


**Required information for RVU in
COMMISSION REGULATION (EU) No. 1254/2014 ANNEX IV**


(a)	Supplier's name	MITSUBISHI ELECTRIC CORPORATION
(b)	Model name	VL-80EU5-E
(c)	SEC (kWh/(m ² .a))	Cold: -51.9 Average: -23.2 Warm: -4.1
(d)	Declared typology	RVU,BVU
(e)	Type of drive	2-speed
(f)	Type of HRS	Recuperative
(g)	Thermal efficiency (%)	62.0
(h)	Maximum flow rate (m ³ /h)	80
(i)	Electric power input (W)	28
(j)	Casing sound power level (dB)	52
(k)	Reference flow rate (m ³ /s)	0.022
(l)	Reference pressure difference (Pa)	0
(m)	SPI (W/(m ³ /h))	0.35
(n)	Control factor and typology	Manual control (no DCV)
(o)	Maximum leakage rate (%)	13%
(p)	Mixing rate of non-ducted	10%
(q)	Visual filter warning	—
(r)	Instructions to install regulated supply/exhaust grilles for unidirectional ventilation	—
(s)	Internet address for disassembly instructions	http://erp.mitsubishielectric.eu
(t)	Airflow sensitivity for non-ducted units	20%
(u)	air tightness for non-ducted units (m ³ /h)	15
(v)	AEC (kWh/a)	Cold: 10.6 Average: 5.3 Warm: 4.8
(w)	AHS (kWh primary energy/a)	Cold: 69.8 Average: 35.7 Warm: 16.1

Manufactured by: **MITSUBISHI ELECTRIC CORPORATION**

TOKYO BLDG. 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO, 100-8310 JAPAN


N24SGGU0006


 **ENERG** Y UA
енергия · ενεργεια IE IA

 **VL-80U5-E/VL-80EU5-E**

A+
A
B
C
D
E
F
G

C

52 dB


80m³/h


ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI
2016 1254/2014