



ENERG

енергия · ενέργεια

Y IJA
IE IA



MITSUBISHI
ELECTRIC

Model

Indoor unit
Outdoor unit

PEAD-M71JAL
PUHZ-ZRP71VHA2

SEER



kW 7,1

SEER 6,0

kWh/yıl 411

A+



SCOP



kW X

SCOP X

kWh/yıl X

A



4,9

X

3,9

X

1762

X



58dB



67dB



ENERJİ · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

626/2011

Ⓐ	Model	Ⓑ Indoor unit	PEAD-M35JAL	PEAD-M50JAL	PEAD-M60JAL	PEAD-M71JAL
		Ⓒ Outdoor unit	PUHZ-ZRP35VKA2	PUHZ-ZRP50VKA2	PUHZ-ZRP60VHA2	PUHZ-ZRP71VHA2
Ⓑ	Sound power levels on cooling mode	Ⓔ Inside dB Ⓕ Outside dB	54 65	59 65	55 67	58 67
Ⓒ	Refrigerant		R410A GWP 1975 *1			
Ⓓ	Cooling	SEER	6,1	6,0	6,2	6,0
Ⓔ		Energy efficiency class	A++	A+	A++	A+
Ⓕ		Annual electricity consumption *2 kWh/a	205	288	340	411
Ⓖ		Design load kW	3,6	5,0	6,1	7,1
Ⓗ	Heating (Average season)	SCOP	4,0	4,3	4,1	3,9
Ⓘ		Energy efficiency class	A+	A+	A+	A
Ⓛ		Annual electricity consumption *2 kWh/a	839	1231	1513	1762
Ⓜ		Design load kW	2,4	3,8	4,4	4,9
Ⓝ	Declarative capacity	(P) at reference design temperature kW	2,4 (-10°C)	3,8 (-10°C)	4,4 (-10°C)	4,9 (-10°C)
Ⓞ		(R) at bivalent temperature kW	2,4 (-10°C)	3,8 (-10°C)	4,4 (-10°C)	4,9 (-10°C)
Ⓟ		(S) at operation limit temperature kW	2,2 (-20°C)	3,7 (-20°C)	2,8 (-20°C)	3,7 (-20°C)
Ⓣ	Back up heating capacity	kW	0	0	0	0

Deutsch	Italiano	Svenska	Polski	Eesti	Malti	Русский
Français	Ελληνικά	Česky	Slovensko	Gaeilge	Suomi	Norsk
Nederlands	Português	Slovensky	Български	Latviski	Türkçe	Українська
Español	Dansk	Magyar	Română	Lietuvių k.	Hrvatski	
Model	Modello	Modell	Model	Model	Model	Модель
Modèle	Модéло	Model	Model	Déanamh	Malli	Модell
Model	Modelo	Model	Модел	Modelis	Model	Модель
Modelo	Model	Modell	Model	Modelis	Model	Модель
Innengerät	Unità interna	Inomhusenhet	Jednostka wewnętrzna	Sisesade	Unità għal ġewwa	Внутренний прибор
Appareil intérieur	Εσωτερική μονάδα	Vnitřní jednotka	Notranja enota	Aonad laistigh	Sisáksikkó	Innendørsenhet
Binnenunit	Unidade interior	Vnútorná jednotka	Вътрешно тяло	Iekšelpu ierice	İç ünite	Внутрішній блок
Unidad interior	Indendørsenhet	Beltéri egység	Unitate de interior	Patalpoje montuojamas irenginys	Unutarnja jedinica	
Außengerät	Unità esterna	Utomhusenhet	Jednostka zewnętrzna	Välisseade	Unità għal barra	Наружный прибор
Modèle extérieur	Εξωτερική μονάδα	Vnější jednotka	Zunanja enota	Aonad lasmuigh	Ulkoysikkö	Utendørsenhet
Buitenunit	Unidade exterior	Vonkajšia jednotka	Външно тяло	Ārtelpas ierice	Diş ünite	Зовнішній блок
Unidad exterior	Udendørsenhet	Kültéri egység	Unitate de exterior	Lauke montuojamas irenginys	Vanjska jedinica	
Schalleistungspegel im Kühlmodus	Livelli di potenza sonora in modalità di raffreddamento	Bullernivå i nedkylningsläget	Poziom moczy dźwięku w trybie chłodzenia	Mūratasemed jahutusrežiimis	Livelli tal-qawwa tal-hsejjes fil-modalità tat-kessieħ	Значения уровня звуковой мощности в режиме охлаждения
Niveaux de puissance corrects en mode de refroidissement	Επίπεδα ισχύος ρήχου στην κατάσταση ψύξης	Úrovně hlučnosti v režimu chlazení	Ravni zvočne moči v načinu hlajenja	Leibhéil chumhacha fuaime ar mhodh fuaralhe	Äänenvoimakkuustasot viilenystillassa	Lydrykknivär i avkjölingsmodus
Geluidsniveaus in koelstand	Níveis de potência sonora em modo de arrefecimento	Hladiny akustického výkonu v režime chladenia	Нива на звукового мощност в режиме охлаждане	Akustiskās jaudas līmenis dzesēšanas režīmā	Soğutma modunda ses güç düzeyleri	Рівні звукової потужності у режимі охолодження
Niveles de potencia del sonido en el modo de refrigeración	Lydstyrkeniveauer i kølefunktion	Hangnyomásszintek hűtés üzem-módban	Nivel sonor în modul de răcire	Garso galios lygis vésinimo režimu	Razine zvučnog tlaka pri hlađenju	
Innen	Interno	Insida	Wewnätrz	Sees	Gewwa	Внутри
À l'intérieur	Εσωτερικό	Uvnitř	Znotraj	Laistigh	Sisäpuoli	Innwendig
Binnenkant	Interior	Vo vnútri	Вътре	Iekštelpās	İç taraf	Усередині
Interior	Indvendig	Bent	Interior	Vidinis	Unutra	
Außen	Externo	Utsida	Na zewnätrz	Väljas	Barra	Снаружи
À l'extérieur	Εξωτερικό	Venu	Zunaj	Lasmuigh	Ulkopuoli	Utwendig
Buitenkant	Exterior	Vonku	На открыто	Ārtelpā	Diş taraf	Назовні
Exterior	Udvendig	A szabadban	Exterior	İsorinis	Vani	
Kühlmittel	Refrigerante	Köldmedel	Czynnik chłodniczy	Külmutsagens	Refrigerant	Хладагент
Réfrigérant	Ψυκτικό	Chladivo	Hladilno sredstvo	Cuisnéan	Kylmääine	Kjølemedium
Koelmiddel	Refrigerante	Chladivo	Xladilen agent	Aukstumaģents	Soğutucu	Холодаагент
Refrigerante	Kølemiddel	Hütöközeg	Refrigerent	Šaldalas	Rashladno sredstvo	

Deutsch	Italiano	Svenska	Polski	Eesti	Malti	Русский
Français	Ελληνικά	Česky	Slovensko	Gaeilge	Suomi	Norsk
Nederlands	Português	Slovensky	Български	Latviski	Türkçe	Українська
Español	Dansk	Magyar	Română	Lietuvių k.	Hrvatski	
Kühlen	Raffreddamento	Kyla	Chłodzenie	Jahutus	Tkessiħ	Охлаждение
Refroidissement	Ψύξη	Chlazení	Hlajenie	Fuarú	Vilennys	Avkjøling
Koelen	Arrefecimento	Chladenie	Oxhlađanje	Dzesēšana	Soğutma	Охолодження
Refrigeración	Köling	Hűtés	Răcire	Vésinimas	Hlađenje	
Energieeffizienzklasse	Classe di efficienza energetica	Energiklass	Klasa energetyczna	Energiatħosħuse klass	Klassi tal-effiċjenza fl-użu tal-enerġija	Класс эффективности использования энергии
Classe d'efficacité énergétique	Κλάση ενέργειακής απόδοσης	Třída energetické účinnosti	Razred energetske učinkovitosti	Aicme ēifeachtulachha fuinnimh	Energiatehokkuusluokka	Energieffektivitetsklasse
Energie-efficiëntiekklasse	Classe de eficiència energética	Trieda energetickej účinnosti	Klasc na energetična efektivnost	Energoefektivitātes klase	Enerji verimlilik sıñi	Клас ефективності енергоспоживання
Clase de eficiencia energética	Energieeffektivitetsklasse	Energiahátekonyásig osztály	Clasă de eficiență energetică	Energijs vartojimo efektyvumo klasė	Klasa energetiske učinkovitosti	
Jahresstromverbrauch *2	Consumo annuale di energia elettrica *2	Årlig strömförbrukning *2	Zužycie prądu w skali roku *2	Aastane voolutarbirbus *2	Konsum annwali tal-elettriku *2	Годовое потребление электроэнергии *2
Consommation d'électricité annuelle *2	Ετήσια κατανάλωση πεύματος *2	Roční spotřeba elektrické energie *2	Letna poraba elektrike *2	Ídiu leictreachais bhliantúl *2	Vuotuinen sähkökulutus *2	Årlig strømforbruk *2
Jaarlijks elektriciteitsverbruik *2	Consumo anual de electricidadade *2	Ročná spotreba elektriny *2	Годишка консумация на електроенергия *2	Gada elektroenerģijas patēriņš *2	Yıllık elektrik tüketimi *2	Річне споживання електроенергії *2
Consumo anual de electricidad *2	Arligt elforbrug *2	Éves áramfogyasztás *2	Consum anual de electricitate *2	Metinis elektros energijos suvarojimas *2	Godišnja potrošnja električne energije *2	
Lastauslegung	Carico nominale	Dimensionerande belastning	Maksymalne obciążenie	Projekteeritud koormus	Tagħbija tad-disinn	Расчетная нагрузка
Charge de calcul	Σχεδιασμός, φόρτωσης	Jmenovité zatížení	Nazivna obremenitev	Lód dearrha	Laskettu kuormitus	Uformningsbelastning
Ontwerpbelasting	Carga nominal	Projektované zaťaženie	Проектен товар	Aprēķina slodze	Tasarim yükü	Розрахункове навантаження
Carga de diseño	Brugslast	Méretezési terhelés	Sarcină nominală	Projektinė apkrova	Težina uređaja	
Heizen (Jahresdurchschnitt / wärmeres Wetter)	Riscaldamento (Stagione media / calda)	Värme (Genomsnittlig/varmare årtid)	Ogrzewanie (Sezon umiarkowany/ciepły)	Kütmine (keskmene/soojaperiood)	Tishin (Stağun Medju / Aktar Shun)	Харрев (средний/теплый сезон)
Chauffage (moyenne saison / saison chaude)	Θέρμανση (Εποχή με μέσες / υψηλότερες θερμοκρασίες)	Topení (průměrná/teplá sezóna)	Ogrevanje (Povprečni/toplejši letni čas)	Téamh (Séasúr Meánach / Níos teo)	Lämmitys (Normaalii / Lämpimämpi kausi)	Oppvarming (gjennomsnittlig / varmere årstid)
Verwärmen (gemiddeld / warmer seizoen)	Aquecimento (Média estação / estação mais quente)	Vykurovanie (Priemerné/teplejšie obdobie)	Отопление (Средно / Топъл сезон)	Sildišana (Vidēji siltā/siltā gadalaikā)	İsıtma (Ortalama / İlik mevsim)	Опалення (у середній/теплий сезон)
Calefacción (Promedio / temperatura más cálida)	Varme (gennemsnittlig/varmre sæson)	Fűtés (Átlagos/meleg évszak)	Încălzire (Anotimp normal/mai cald)	Šildymas (vidutinis / šiltuoju sezonu)	Zagrijavanje (Prosječ / toplica sezona)	
Nennkapazität	Capacità dichiarata	Deklarerad kapacitet	Deklarowana pojemność	Deklareritudo vőimsus	Kapaċità ddikjarata	Гарантированная мощность
Capacité déclarée	Δηλωμένη χωρητικότητα	Udávaná kapacita	Prijavljena zmogljivost	Toileadħi fogaṛtha	Ilmoitettu teho	Erklært kapasitet
Aangegeven capaciteit	Capacidade declarada	Deklarovaný výkon	Обявена мощност	Deklarētā jauda	Beyan edilen kapasite	Гарантована потужність
Capacidad declarada	Erkläret kapacitet	Névleges teljesítmény	Capacitate declarată	Deklaruotas pajęgumas	Deklarirani kapacitet	
bei angegebener Referenztemperatur	alla temperatura di progetto di riferimento	vid dimensionerande referenstemperatur	w znamionowej temperaturze odniesienia	projekteerimise vörðlustemperaturu juures	f'temperatura tad-disinn ta' referenza	при эталонной расчетной температуре
à la température de calcul de référence	σε θερμοκρασία σχεδιασμού αναφοράς	při referenční výpočtové teplotě	ob referenční nazivní temperaturi	ag teocht dearthu tagartha	perusmittoitulämpötilassa	ved referansetemperatur for utforming
bij referentieontwerptemperatuur	à températura nominal de referência	pri referenčnej výpočtové teplotě	pri izčislitelna projektna temperatūra	aprēķina references temperatūrā	referans tasaram sicaklığında	При етапной розрахунковій температурі
a temperatura de diseño de referencia	ved brugsafhængig referencetemperatur	tervezési referencia-hőmérsékleten	la temperatura de referință nominală	esant norminei projektnie temperatură	pri referentnoj temperaturi	
bei bivalenter Temperatur	alla temperaturla bivalente	vid bivalent temperatur	w temperaturze biwalentnej	bivalentse temperatuuri juures	f'temperatura bivalenti	при бивалентной температуре
à température bivalente	σε θερμοκρασία δισθενούς λειτουργίας	při bivalentní teplotě	pri bivalentní temperaturi	ag teocht dhéfiúsach	kaksiarvoisessa lämpötilassa	ved bivalent temperatur
bij bivaleente temperatuur	à temperatura bivalente	pri bivalentnej teplotě	pri			

PRODUCT INFORMATION (*)

PACKAGED AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	PEAD-M71JAL PUHZ-ZRP71VHA2
--------------------------	-------------------------------	-------------------------------

Function (indicate if present)		If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season	
cooling	Y	Average (mandatory)	Y
heating	Y	Warmer (if designated)	N
		Colder (if designated)	N

Item	symbol	value	unit
Design load			
cooling	Pdesignc	7.1	kW
heating/Average	Pdesignh	4.9	kW
heating/Warmer	Pdesignh	x	kW
heating/Colder	Pdesignh	x	kW

Item	symbol	value	unit
Seasonal efficiency			
cooling	SEER	6.0	-
heating/Average	SCOP/A	3.9	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	7.1	kW
Tj=30°C	Pdc	5.2	kW
Tj=25°C	Pdc	3.3	kW
Tj=20°C	Pdc	2.2	kW

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	EERd	3.6	-
Tj=30°C	EERd	5.2	-
Tj=25°C	EERd	8.0	-
Tj=20°C	EERd	9.0	-

Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	4.3	kW
Tj=2°C	Pdh	2.6	kW
Tj=7°C	Pdh	2.2	kW
Tj=12°C	Pdh	2.0	kW
Tj=bivalent temperature	Pdh	4.9	kW
Tj=operating limit	Pdh	3.7	kW

Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	2.7	-
Tj=2°C	COPd	4.1	-
Tj=7°C	COPd	4.5	-
Tj=12°C	COPd	6.0	-
Tj=bivalent temperature	COPd	2.4	-
Tj=operating limit	COPd	2.3	-

Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW

Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	COPd	x	-
Tj=7°C	COPd	x	-
Tj=12°C	COPd	x	-
Tj=bivalent temperature	COPd	x	-
Tj=operating limit	COPd	x	-

Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x	kW
Tj=2°C	Pdh	x	kW
Tj=7°C	Pdh	x	kW
Tj=12°C	Pdh	x	kW
Tj=bivalent temperature	Pdh	x	kW
Tj=operating limit	Pdh	x	kW
Tj=-15°C	Pdh	x	kW

Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	COPd	x	-
Tj=2°C	COPd	x	-
Tj=7°C	COPd	x	-
Tj=12°C	COPd	x	-
Tj=bivalent temperature	COPd	x	-
Tj=operating limit	COPd	x	-
Tj=-15°C	COPd	x	-

Bivalent temperature			
heating/Average	Tbiv	-10	°C
heating/Warmer	Tbiv	x	°C
heating/Colder	Tbiv	x	°C

Operating limit temperature			
heating/Average	Tol	-20	°C
heating/Warmer	Tol	x	°C
heating/Colder	Tol	x	°C

Cycling interval capacity			
for cooling	Pcycc	x	kW
for heating	Pcych	x	kW
Degradation co-efficient cooling	Cdc	0.25	-

Cycling interval efficiency			
for cooling	EERcyc	x	-
for heating	COPcyc	x	-
Degradation co-efficient heating	Cdh	0.25	-

Electric power input in power modes other than 'active mode'			
off mode	POFF	15	W
standby mode	PSB	15	W
thermostat - off mode	PTO(c/h)	26/26	W
crankcase heater mode	PCK	0	W

Annual electricity consumption			
cooling	QCE	411	kWh/a
heating/Average	QHE	1762	kWh/a
heating/Warmer	QHE	x	kWh/a
heating/Colder	QHE	x	kWh/a

Capacity control (indicate one of three options)			
fixed	N		
staged	N		
variable	Y		

Other items			
Sound power level (indoor/outdoor)	LWA	58/67	dB(A)
Global warming potential	GWP	1975	kgCO2eq
Rated air flow (indoor/outdoor)	-	1500/3300	m3/h

Contact details for obtaining more information	Name and address of the manufacturer or of its authorized representative.
--	---

(*) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012.

TECHNICAL DOCUMENTATION (1)

PACKAGED AIR CONDITIONER	INDOOR MODEL OUTDOOR MODEL	PEAD-M71JAL PUHZ-ZRP71VHA2	250H1100W732D (mm) 943H950W330D (mm)
--------------------------	-------------------------------	-------------------------------	---

Function	
cooling	Y
heating	Y

The heating season	
Average (mandatory)	Y
Warmer (if designated)	N
Colder (if designated)	N

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
Seasonal efficiency (2)			
cooling	SEER	6.0	-
heating/Average	SCOP/A	3.9	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Energy efficiency class			
cooling	SEER	A+	-
heating/Average	SCOP/A	A	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Other items			
Sound power level (indoor/outdoor)	LWA	58/67	dB(A)
Refrigerant	-	R410A	-
Global warming potential	GWP	1975	kgCO2eq.

identification and signature
of the person empowered to
bind the supplier

Tomoyuki Miwa
Manager,
Packaged Air Conditioners Quality Control Section
MITSHUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS

(1) This information is based on COMMISSION DELEGATED REGULATION (EU)No626/2011.

(2) SEER/SCOP values are measured based on FprEN 14825:2011: Testing and rating at part load conditions and calculation of seasonal performance.